

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior listings and versions of claims in the application:

Listing of Claims:

1. (Currently Amended) A method for performing a supervised learning process in an artificial intelligence environment within a computer system, the method including optimizing a database of sample records for the training and testing of a prediction algorithm for predicting the presence or absence of a specified medical condition in a patient, the method comprising the steps of:

defining a set of one or more distributions of the database records onto respective training and testing subsets;

using the defined set of distributions to train and test a first generation set of one or more prediction algorithms and assigning a fitness score to each, each of said prediction algorithms being associated with a certain distribution of said database records;

feeding the set of prediction algorithms to an evolutionary algorithm which generates a set of one or more second generation prediction algorithms and assigns a fitness score to each; and

continuing to feed each generational set of prediction algorithms to the evolutionary algorithm until a termination event occurs, where-wherein said termination event is at least one of:

a prediction algorithm [[is]] generated with a fitness score equal to or exceeding a defined minimum value,

the maximum fitness score of successive generational sets of prediction algorithms converging to a given value, and/or

a certain number of generations having been generated;

selecting a prediction algorithm having a best fitness score; and

using the distribution of database records associated with said selected prediction algorithm in performing supervised learning, said supervised learning including training and testing of prediction algorithms to obtain a trained prediction algorithm, wherein

said method is performed using a computer and computer software forming an intelligent system, and

the trained prediction algorithm is effective to predict output variables for data relating to said condition, thereby predicting diagnosis of said condition,
~~and the method~~ further comprising the steps of:

generating a population of prediction algorithms, ~~where wherein~~ each one of said prediction algorithms is trained and tested according to a different distribution of the records of the data set in the complete database onto a training data set and a testing data set,

each different distribution being created as one or more of a random distribution ~~and a distribution formed by a deterministic mathematical process characterized as or a~~ pseudorandom distribution,

each prediction algorithm of ~~[[the]]~~ said population being trained according to its own distribution of records of the training set and ~~[[is]]~~ being validated in a blind way according to its own distribution on the testing set, and

a score reached by each prediction algorithm being calculated in the testing phase representing its fitness;

providing an evolutionary algorithm which combines the different models of distribution of the records of the complete data set in a training and in a testing set, which sets are represented each one by a corresponding prediction algorithm trained and tested on the basis of ~~[[the]]~~ said training and testing data set according to the fitness score calculated in the previous step for the corresponding prediction algorithm,

the fitness score of each prediction algorithm corresponding to one of the different distributions of the complete data set on the training and the testing data sets being the probability of evolution of each prediction algorithm or of each said distribution of the complete data set on the training and testing data sets;

repeating the evolution of the prediction algorithm generation for a finite number of

generations or till the output of the genetic algorithm converges to a best solution and/or till the fitness value of at least some prediction algorithm related to an associated data records distribution has reached a desired value; and

setting the data records distribution for the best solution as the optimized training and testing subsets for training and testing prediction algorithm.

2. (Cancelled)

3. (Currently Amended) A method according to claim 1, ~~characterised in that~~wherein to each record of the data set a distribution variable is associated which is binary and has at least two ~~status~~ statuses, one of this two ~~status~~ statuses being associated with the inclusion of the record in the training set and the other in the testing set.

4. (Currently Amended) A method according to claim 1, ~~characterised that~~wherein the prediction algorithm is an artificial neural network.

5. (Currently Amended) A method according to claim 1, ~~characterised in that~~wherein the prediction algorithm is a classification algorithm.

6. (Currently Amended) A method according to claim 1, ~~characterised in that~~wherein once an optimum distribution has been computed, the ~~optimised~~ optimized training data subset is made equal to a complete data set being the individuals included in the training subset distributed onto a new training set and onto a new testing set each one having about the half of the records of the original optimized training set, while the originally optimized testing set is used as a third data subset for validation purposes.

7. (Currently Amended) A method according to claim 6, ~~characterised in that~~wherein the distribution of the data of the originally optimized training set onto the new training and new testing set is optimized ~~by means of~~ through a pre-processing phase including the steps of said method for optimizing a database of sample records, said records being

records in the originally optimized training set.

8. (Currently Amended) A method according to claim 1, ~~in which~~ wherein different choices of the structure of the training subset and the structure of the testing subset consist in different selections of the number of input variables of the data records of the database, which selections consist in leaving out at least one, ~~preferably two or more variables~~ variable from the entire input variable set forming each record, the records of the database comprising a certain number of known input variables and a certain number of known output variables.

9. (Currently Amended) A method according to claim 8, ~~characterised by further comprising~~ the following steps:

defining a distribution of data from the complete data set onto a training data set and onto a testing data set;

generating a population of different prediction algorithms each one having a training and/or testing data set in which only some variables have been considered among all the original variables provided in the data sets, each one of the prediction algorithms being generated ~~by means of~~ through a different selection of variables;

carrying out learning and testing of each prediction algorithm of the population and evaluating the fitness score of each prediction algorithm;

applying an evolutionary algorithm to the population of prediction algorithms for achieving new generations of prediction algorithm;

for each generation of new prediction algorithms representing each one a new different selection of input variable, testing or validating the best prediction algorithm according to the best hypothesis of input variables selection ~~is tested or validated; and~~

evaluating a fitness score ~~is evaluated and~~ promoting the prediction algorithms, representing the selections of input variables which have the best testing performances and the minimum input variables, ~~are promoted~~ for the processing of the new generations.

10. (Currently Amended) A method according to claim 8, further comprising a pre-processing phase, including the steps of said method for optimizing a database of sample

records, for selecting the most predictive input variables.

11. (Currently Amended) A method according to claim 1,

~~in which wherein~~ different choices of the structure of the training subset and the structure of the testing subset ~~consist in comprise~~ different selections of the number of input variables of the data records of the database, which selections ~~consist in comprise~~ leaving out at least one, preferably two or more variables variable from the entire input variable set forming each record, the records of the database comprising a certain number of known input variables and a certain number of known output variables,

and further comprising a pre-processing phase, including the steps of said method for optimizing a database of sample records, for selecting the most predictive input variables,

~~characterised in that wherein~~ the database subjected to the a pre-processing phase of input variable selection is a training subset and a testing subset processed with said method.

12. (Currently amended) A method according to claim 1, ~~characterised in that wherein~~ the complete database, the distribution of the records of which has to be optimized, has data records having a selected number of input variables, the selection being carried out with said method, and in which different choices of the structure of the training subset and the structure of the testing subset ~~consist in comprise~~ different selections of the number of input variables of the data records of the database, which selections ~~consist in comprise~~ leaving out at least one, preferably two or more variables variable from the entire input variable set forming each record, the records of the database comprising a certain number of known input variables and a certain number of known output variables.

13. (Currently Amended) A method according to claim 1, ~~characterised in that wherein~~ a preprocessing phase for optimizing the distribution of the records on a training subset and a testing subset and for selecting the most predictive input variables[[,]] is carried out alternatively one to the other several times.

14. (Currently Amended) A method according to claim 1, ~~characterised in~~

~~that~~wherein the evolutionary algorithm is a genetic algorithm with the following evolutionary rules:

an average health value of the population is computed as a function of the fitness values of each single individual in the population;

coupling, recombination of genes and mutation of genes are carried out in a differentiated manner depending on a comparison between the fitness of each individual of the couple and the average health value of the entire population to which the individuals belong;

individuals having a fitness value lower or equal to the average health of the entire population are not excluded from the creation of new generations but are marked out and entered in a vulnerability list; and

the number of subjects entered in the vulnerability list defining the number of possible marriages.

15. (Currently Amended) A method according to claim 14, ~~characterised in that~~wherein for coupling purposes and for generation of children at least one parent individuals must have a fitness value greater than the average health value of the population.

16. (Currently Amended) A method according to claim 14, ~~characterised in that~~wherein each couple of individuals can generate ~~individuals~~ offsprings having a fitness different from the average health, ~~so called offsprings~~ if the fitness of one them, at least is greater than the average fitness, the ~~offsprings~~ of each marriage occupying the places of subjects entered in the vulnerability list ~~and~~ which are marked out, so that a weak individual can continue to exist through his own children.

17. (Currently Amended) A method according to claim 14, ~~characterised in that~~wherein coupling between individuals having a very low fitness value and a very high fitness value are not allowed.

18. (Currently Amended) A method according to claim 14, ~~characterised in that~~wherein the following recombination rules of the genes of the parents individuals coupled

are considered in the case the parents individuals have not common genes:

the health of father and mother individuals are greater than the average health of the entire population; the crossover is a classical crossover according to which the genes of the father and of the mother individuals are substituted one with the other starting from a certain crossover point;

the health of father and mother individuals are lower than the average health of the entire population; ~~in this~~, in which case the two children are formed through rejection of the parents genes they will receive by the crossover process;

the health of one of the parents is less than the average health of the entire population while the health of the other parent is greater than the average health of the entire population; ~~in this~~, in which case only the parents whose health is greater than the average health of the entire population will transmit their genes, while the genes of the parent having an health lower than the average health of the entire population are rejected.

19. (Currently Amended) A method according to claim 18, wherein each gene is ~~characterised~~ characterized by a status level, ~~the method further characterised in that and wherein~~ genes rejection ~~consists in~~ comprises modifying the status of the genes from one status level to a different status level.

20. (Currently Amended) A method according to claim 18, ~~characterised in that wherein~~ a modified crossover of the genes of the parents individuals is carried out when the parents individuals has part of the genes that coincide, this modified crossover ~~provides~~ providing for generating ~~and an~~ offspring in which the genes selected for crossover are the most effective ones of the parents.

21. (Currently Amended) A method according to claim 14, ~~wherein in which~~ the individuals are the different prediction algorithm representing a corresponding different initial random distribution of data records onto the testing and the training data set and the genes ~~consist in~~ comprise the binary status variable of association of each record to the training and to the testing subset.

22. (Currently Amended) A method according to claim 14, ~~wherein in which~~ the individuals are the prediction algorithms each one representing a different training and testing data set, the difference residing in a different selection of input variables for each different training and testing subset, and wherein the genes ~~consist in~~ comprise the different selection variable which is provided for each input variable in the different training and testing subsets, the above mentioned selection variable being a parameter indicating the presence/absence of each corresponding input variable in the records of each data set.

23. (Currently Amended) A method according to claim 1, wherein the method ~~characterized in that~~ it is in the form of a software program comprising instructions executable by a CPU, the software program being stored in a memory ~~to which~~ accessible by the CPU ~~can access~~.

24. (Currently Amended) A software program stored on a memory device, wherein the ~~said~~ software program consisting in the method according to claim 1 in the form of [[a]] executable instructions ~~of~~ by a CPU or ~~of~~ by a computer system.

25. (Currently Amended) A system for carrying out a method according to claim 1, comprising:

an apparatus or device for generating an action of response which is autonomously, ~~i.e. by itself,~~ chosen among a certain number of different kinds of actions of response stored in a memory of the apparatus or autonomously generated by the apparatus basing the ~~said~~ choice of the kind of action of response on the interpretation of data collected autonomously by ~~means of~~ one or more sensors responsive to physical entities or which are fed to the apparatus by ~~means of~~ input means, the said interpretation being made ~~by means of~~ through a prediction algorithm in the form of [[a]] software saved in a memory of ~~the said~~ apparatus and being carried out by a central processing unit,

~~characterized in that~~ wherein the apparatus ~~being is~~ further provided with means for carrying out a training and testing phase of the prediction algorithm by inputting to the said prediction algorithm data of a known database, in which input variables of the input data representing the physical entities ~~able to be~~ sensed by the apparatus through the one or

more sensors and/or ~~able to be fed~~ to the apparatus by ~~means of~~ the input means are univoquely correlated to at least one definite kind of action of response among the different kinds of possible action of response, the ~~said~~ means for carrying out the training an testing being in the form of a training and testing software saved in a memory of the apparatus, the ~~said~~ training and testing being carried out by ~~means of~~ a method according to claim 1, the ~~said~~ training and testing software program being ~~the said~~ method of training and testing in the form of a software program or instructions.

26. (Currently Amended) The system according to claim 25, ~~characterized in that it~~ wherein the system is a system for sound or vocal recognition comprising input means responsive to acoustic waves, a processing unit connected to the input means responsive to acoustic waves, at least a memory in which a software program is stored, ~~the said~~ program being in the form according to claims 23 or 24 and comprising coded instructions for enabling the processing unit to carry out a method according to claim 1, a further or the same above mentioned memory, in which a dataset of known data records is stored or ~~can be stored~~ storable and/or input means for storing in the further or ~~the said~~ above mentioned memory a dataset of known data records.

27. (Currently Amended) The system according to claim 25, ~~characterized in that it~~ wherein the system is a system for image recognition, the input means being ~~responsible~~ responsive to electromagnetic waves, the system being ~~able~~ configured to recognize the shape of an object generating or reflecting electromagnetic waves, and/or the distance and/or the identity of the object.

28. (Currently Amended) The system according to claim 26, ~~characterized in that~~ wherein the database of known data records comprises acoustic signals emitted by one or more objects or one or more living beings making part of the typical environment in which the device has to operate or the data relating to one or more images of one or more objects or one or more living beings making part of the typical environment in which the device has to operate, to which are univoquely correlated to corresponding known kind, and/or identity and/or meaning of objects to which ~~the said~~ acoustic signals or image data are related and/or from which ~~the said~~ acoustic signals or image data are generated.

29. (Currently Amended) The system according to claim 27, ~~characterized in that it~~
~~-wherein the system~~ is a specialized system for image pattern recognition having
artificial intelligence utilities for analyzing ~~a digitalized image, i.e., an image in the form of a array~~
of image data records, each image data record being related to a zone or point or unitary area
or volume of a two or three dimensional visual image, ~~so-called pixel or voxel of a visual image,~~
the said visual image being formed by an array of the said pixels or voxels and utilities for
indicating for each image data record a certain quality among a plurality of known qualities of
the image data records;

the system having a processing unit ~~as for example a conventional computer,~~ a memory
in which an image pattern recognition algorithm is stored in the form of a software program
which can be executed by the processing unit;

a memory in which a certain number of predetermined different qualities which the
image data records ~~can be configured to~~ assume has been stored and which qualities ~~has have~~
to be univoquely associated to each of the image data records of an image data array fed to the
system;

input means for receiving arrays of digital image data records or input means for
generating arrays of digital image data records from an existing image and a memory for storing
~~the said~~ digital image data array;

output means for indicating for each image data record of the image data array a certain
quality chosen by the processing unit in carrying out the image pattern recognition algorithm in
the form of ~~the said~~ software program;

the image pattern recognition algorithm ~~is being~~ a prediction algorithm in the form of a
software program, which prediction algorithm is further associated to a system being further
provided with a training and testing software program;

the system ~~is able being configured~~ to carry out training and testing according to the
method of claim 1;

the method ~~is being~~ provided in the system in the form of the training and testing
software program; and

a database being also provided in which data records are contained univoquely
associating known image data records of known image data arrays with the corresponding

known quality from a certain number of predetermined different qualities, which the image data records can be configured to assume.

30. (Currently Amended) A method for producing a microarray for genotyping operations, the ~~said~~ method comprising the steps of defining a certain number of theoretically relevant genes or alleles or polymorphisms considered relevant for a certain biologic condition like a tissue structure, a pathology or the potentiality of developing a pathology or an anatomic or morphologic feature, the method comprising:

[[a)]] providing a database of experimentally determined data in which each record relates to a known clinical or experimental case of a sample population of cases, ~~and~~ which records comprise a certain number of input variables corresponding to the presence/absence of a certain predetermined number of polymorphisms and/or mutations and/or equivalent genes of a certain number of theoretically probable relevant genes, said certain predetermined number of polymorphisms and/or genes forming a set, and one or more related output variables corresponding to the certain biological or pathologic condition of the ~~said~~ clinical and experimental cases of the sample population;
~~characterized by the following further steps:~~

[[b)]] determining a selection of a subset of the set of certain predetermined number of polymorphisms and/or genes by testing the association of the ~~said~~ genes or polymorphisms and the biological or pathological condition by ~~means of~~ mathematical tools applied to the database;

[[c)]] the ~~said~~ mathematical tools ~~comprise~~ comprising a ~~so-called~~ prediction algorithm ~~such as a so-called neural network;~~

~~and the further steps are carried out of:~~

[[d)]] dividing the database into a training and a testing dataset for training and testing the prediction algorithm;

[[e)]] defining two or more different training datasets each one having records with a set of input variables obtained by excluding one or more input variables from the originally defined number of input variables, while for each record the set of input variables of the corresponding training set has at least one input variable which is not a member of the set of input variables of the other training datasets, each said at least one input variable ~~consisting in~~ comprising a different gene or a different polymorphism[[s]] and/or a different mutation and/or a different

functionally equivalent gene thereof of the originally considered genes or polymorphisms and/or mutations and/or functionally equivalent genes thereof considered theoretically potentially relevant for the biologic or pathologic condition;

[[f)]] training the prediction algorithm with each of the different training sets defined under point-e) at the previous step for generating a first population of different prediction algorithms which are divided into two groups of mother and father prediction algorithms and testing the said prediction algorithms with the associated testing set;

[[g)]] calculating a fitness score or prediction accuracy of each father and mother prediction algorithms of the said first population ~~by means of~~ through the testing results;

[[i)]] providing a ~~so-called~~ an evolutionary algorithm such as a genetic algorithm and applying the evolutionary algorithm to the first population of mother and father prediction algorithms for achieving new generation of prediction algorithms whose training and testing dataset comprises records whose input variables selections are a combination of the input variable selections of the records of the training and of the testing datasets of the first or previous population of father and mother prediction algorithms according to the rules of the evolutionary algorithm;

[[j)]] for each generation of new prediction algorithms representing each new variant selection of input variables, the best prediction algorithm according to the best hypothesis of input variable selection [[is]] being tested or validated ~~by means of~~ through the testing dataset;

[[k)]] evaluating a fitness score ~~is evaluated~~ and the promoting prediction algorithms representing the selections of input variables which have the best testing performance with the minimum number of input variables utilized ~~are promoted~~ for the processing of new generations;

[[l)]] repeating the preceding two steps i) to k) until a predetermined fitness score defined as best fit of the prediction algorithm and a minimum number of input variables has been reached; and

[[m)]] defining as the selected relevant input variables, the selected input variables comprising i.e. as the relevant genes or polymorphisms and/or of mutations and/or of functionally equivalent genes thereof, the ones related to the input variables of the selection represented by the prediction algorithm having both at least the predetermined fitness score and also the minimum number of selected input variables.

31. (Currently Amended) A method according to claim 30, ~~characterized in that~~
wherein an optimization of the distribution of the records of the original database in a training
dataset and in a testing dataset is carried out in one of a pre processing and a post processing
phase, ~~i.e. before carrying out the steps e) to m) at step d) or after having carried out the steps~~
~~a) to m).~~

32. (Currently Amended) The method according to claim 31, further comprising the
following steps of ~~optimisation~~optimization:

defining a set of one or more distributions of the database records onto respective
training and testing subsets;

using the defined set of distributions to train and test a first generation set of one or more
prediction algorithms and assigning a fitness score to each;

feeding the set of prediction algorithms to an evolutionary algorithm which generates a
set of one or more second generation prediction algorithms and assigns a fitness score to each;
and

continuing to feed each generational set of prediction algorithms to the evolutionary
algorithm until a termination event occurs;

~~where~~ wherein said termination event is at least one of a prediction algorithm is
generated with a fitness score equalling or exceeding a defined minimum value, the maximum
fitness score of successive generational sets of prediction algorithms converging to a given
value, and a certain number of generations having been generated.

33. (Currently Amended) The method according to claim 31, further comprising the
following steps:

generating a population of prediction algorithm each ~~one of them is trained~~ and tested
according to a different distribution of the records of the data set in the complete database onto
a training data set and a testing data set;

each different distribution being created by a random distribution or a distribution formed
by a ~~deterministic mathematical process characterized as a~~ pseudo-random distribution;

each prediction algorithm of the said population is being trained according to its own

distribution of records of the training set and is-being validated in a blind way according to its own distribution on the testing set;

a score reached by each prediction algorithm is-being calculated in the testing phase representing its fitness;

an evolutionary algorithm being further provided which combines the different models of distribution of the records of the complete data set in a training and in a testing set, which sets are represented each one by a corresponding prediction algorithm trained and tested on the basis of the said training and testing data set according to the fitness score calculated in the previous step for the corresponding prediction algorithm;

the fitness score of each prediction algorithm corresponding to one of the different distributions of the complete data set on the training and the testing data sets being the probability of evolution of each prediction algorithm or of each said distribution of the complete data set on the training and testing data sets;

repeating the evolution of the prediction algorithm generation for a finite number of generations or till the output of the genetic algorithm converges to a best solution and/or till the fitness value of at least some prediction algorithm related to an associated data records distribution has reached a desired value; and

setting the data records distribution for the best solution as the optimized training and testing subsets for training and testing prediction algorithm.

34. (Currently Amended) A microarray for genotyping comprising a reduced number of genes, alleles or polymorphisms, ~~characterized in that~~ wherein the reduced number of the said genes, alleles or polymorphisms has been selected ~~by means of~~ with a method according to claim 30.

35. (Currently Amended) A method for performing a supervised learning process in an artificial intelligence environment including optimizing a database of sample records for the training and testing of a prediction algorithm for a problem under investigation characterized by input variables and output variables, the prediction algorithm used for predicting output variables for real world data, the method comprising the steps of:

defining a set of one or more distributions of the database records onto respective

training and testing subsets;

using the defined set of distributions to train and test a first generation set of one or more prediction algorithms and assigning a fitness score to each, each of said prediction algorithms being associated with a certain distribution of said database records;

feeding the set of prediction algorithms to an evolutionary algorithm which generates a set of one or more second generation prediction algorithms and assigns a fitness score to each;

continuing to feed each generational set of prediction algorithms to the evolutionary algorithm until a termination event occurs, where said termination event is at least one of:

a prediction algorithm is generated with a fitness score equal to or exceeding a defined minimum value,

the maximum fitness score of successive generational sets of prediction algorithms converging to a given value, and/or

a certain number of generations having been generated;

selecting a prediction algorithm having a best fitness score;

using the distribution of database records associated with said selected prediction algorithm in performing supervised learning, said supervised learning including training and testing of prediction algorithms to obtain a trained prediction algorithm; and

using the trained prediction algorithm to predict the output variables relating to the problem under investigation where only the input variables are known,

wherein said method is performed using a computer and computer software forming an intelligent system;

the method further comprising the steps of:

generating a population of prediction algorithms, wherein each one of said prediction algorithms is trained and tested according to a different distribution of the records of the data set in the complete database onto a training data set and a testing data set,

each different distribution being created as one or more of a random distribution or a pseudorandom distribution,

each prediction algorithm of [[the]] said population being trained according to its own distribution of records of the training set and [[is]] being validated in a blind way

according its own distribution on the testing set, and

a score reached by each prediction algorithm being calculated in the testing phase representing its fitness;

providing an evolutionary algorithm which combines the different models of distribution of the records of the complete data set in a training and in a testing set, which sets are represented each one by a corresponding prediction algorithm trained and tested on the basis of [[the]] said training and testing data set according to the fitness score calculated in the previous step for the corresponding prediction algorithm.

the fitness score of each prediction algorithm corresponding to one of the different distributions of the complete data set on the training and the testing data sets being the probability of evolution of each prediction algorithm or of each said distribution of the complete data set on the training and testing data sets;

repeating the evolution of the prediction algorithm generation for a finite number of generations or till the output of the genetic algorithm converges to a best solution and/or till the fitness value of at least some prediction algorithm related to an associated data records distribution has reached a desired value; and

setting the data records distribution for the best solution as the optimized training and testing subsets for training and testing prediction algorithm.